## What is claimed is:

1. (Currently Amended) A thermoplastic polyurethane composition, comprising:

the reaction product of

a polyester polyol having a number average of molecular weight of from about 500 to about 5,000;

from about 1 to about 50 parts by weight of a polyether co-polyol comprising poly(tetramethylene ether glycol), poly(propylene oxide), poly(propylene oxide-co-ethylene oxide), polyethylene oxide or combinations thereof per 100 parts by weight of the combined total amount of said polyester polyol and said polyether co-polyol;

a polyisocyanate having the formula R(NCO)<sub>n</sub> where n is an integer of from 2 to 4 and R is an aromatic, cycloaliphatic, aliphatic, or combinations thereof having from 2 to about 20 carbon atoms;

a symmetrical chain extender <u>selected from the group consisting of 1,6-hexanediol, 1,3-propanediol, 1,5-pentanediol, 1,4-butanediol, 1,4-cyclohexanedimethanol (CHDM), hydroquinone di(β-hydroxyethyl)ether (HQEE), 1,4-benzenedimethylol, and combinations thereof;</u>

from about 1 to about 50 moles of a co-chain extender selected from the group consisting of 1,3-butanediol, neopentylglycol, dipropylene glycol, diethylene glycol, di(β-hydroxyethyl) resorcinol, 1,2-propylene glycol, and combinations thereof that is asymmetric or of a different chain length than said symmetrical chain extender or is non-linear or contains a heteroatom co-chain extender per 100 moles of said symmetrical chain extender;

the ratio of the molar <u>percent</u> <u>ratio</u> of said co-chain extender to said symmetrical chain extender to weight percent of said polyether co-polyol to the combined total weight of said polyester polyol and said polyether co-polyol, being from about 0.1 to about 10.

2. (Currently Amended) A thermoplastic polyurethane composition according to claim 1, wherein said co-chain extender comprises 1,3-butanediol, neopentyl glycol, diethylene glycol, dipropylene glycol, di(β-hydroxyethyl) resorcinol or 1,2-propylene glycol, or combinations thereof; and

wherein said reaction product has a reduced annealing value,  $V_t$ , of about 4.0 or less and a sensitivity of the complex viscosity to temperature  $V_{ft}$  ( $(T_m+15)/(T_m+35)$ ) of about 9 or less.

3. (Currently Amended) A thermoplastic polyurethane composition according to claim 2, wherein said symmetrical chain extender comprises 1,6-hexanediol, 1,3-propanediol, 1,5-pentanediol, 1,4-butanediol, 1,4-cyclohexanedimethanol (CHDM), hydroquinone di(β-hydroxyethyl) ether (HQEE), or 1,4-benzenedimethylol, or combinations thereof;

wherein said reaction product has a sensitivity to shear  $V_f$  at  $T_m+15^{\circ}C$  of about 10 or less or a  $V_f$  at  $T_m+35^{\circ}C$  of about 5 or less;

wherein the amount of said polyether co-polyol is from about 2 to about 25 parts by weight per 100 parts by weight of the combined weight of said polyester polyol and said polyether co-polyol, and

wherein the ratio of said molar <u>percent</u> ratio of said co-chain extender to said symmetrical chain extender to the weight percent of said polyether co-polyol to the combined total weight of said polyeter polyol and said polyether co-polyol, is from about 0.15 to about 3.

4. (Currently Amended) A thermoplastic polyurethane composition according to claim 3, wherein the number average molecular weight of said polyester polyol is from about 600 to about 4,000; and

wherein the number average molecular weight of said polyether co-polyol is from about  $250 \ 500$  to about  $5,000 \ 4,000$ , and

Docket No. 202ES048A

Serial No. 10/785,529

October 16, 2007

Page 4

wherein said reaction product has a hydrolytic stability, TS<sub>N</sub>, of about 0.3 or greater.

Claim 5 (Cancelled).

6. (Previously Presented) A thermoplastic polyurethane composition of claim 4 wherein said

co-chain extender is neopentylglycol, dipropylene glycol, 1,3-butanediol, or mixtures thereof.

7. (Currently Amended) A thermoplastic polyurethane composition according to claim 6,

wherein said reduced annealing value V<sub>t</sub> is about 3.5 or less, wherein said V<sub>f</sub> at T<sub>m</sub>+15°C is about

6 or less, and said V<sub>f</sub> at T<sub>m</sub>+35°C is about 4 or less, wherein said polyether co-polyol is

poly(tetramethylene ether glycol), wherein said diisocyanate is MDI or H<sub>12</sub>MDI, or combinations

thereof, wherein said symmetrical chain extender is 1,4-butanediol; and

wherein the ratio of the molar ratio of said co-chain extender to said symmetrical chain

extender to the weight percent of said polyether co-polyol to the combined total weight of said

polyether co-polyol, is from about 0.1 to about 10; and

wherein said co-chain extender is 1,3-butanediol, neopentylglycol, or dipropylene glycol.

Claim 8 (Cancelled).

9. (Currently Amended) A thermoplastic polyurethane composition of claim § 7 wherein the

ratio of the molar percent ratio of said co-chain extender to said symmetrical chain extender to

the weight percent of said polyether co-polyol to the combined total weight of said polyester

polyol and said polyether co-polyol, is from about 0.2 to about 2.

10. (Original) A thermoplastic polyurethane composition according to claim 7, wherein said

polyester polyol is derived from adipic acid, suberic acid, sebacic acid, or azelaic acid, or

combinations thereof with 1,4-butanediol, 1,6-hexanediol, neopentyl glycol, diethylene glycol, or combinations thereof.

- 11. (Original) The thermoplastic polyurethane composition of claim 1, wherein said co-chain extender is used at a level of from about 5 to about 10 moles per 100 moles of said symmetrical chain extender.
- 12. (Previously Presented) The thermoplastic polyurethane composition of claim 11, wherein said polyether co-polyol is used at a level of from about 5 to about 20 parts by weight per 100 parts by weight of the combined total amount of said polyester polyol and said polyether co-polyol.
- 13. (Previously Presented) A thermoplastic polyurethane composition of claim 1 wherein at least four of the following six (A through F) criteria are met:
  - A. a reduced cyrstallinity expressed as  $T_{CN}$  is 0.95 or less,
  - B. an improved hydrolytic stability expressed as  $TS_N$  is 0.3 or greater,
  - C. a reduced sensitivity to shear expressed as  $V_f(T_m+15)$  is 10 or less,
  - D. a reduced sensitivity to shear expressed as  $V_f(T_m + 35)$  is 5 or less,
- E. a sensitivity of the complex viscosity to temperature expressed as  $V_{\rm ft}$  is 10 or less, and
  - F. a reduced annealing expressed as  $V_t$  is 4 or less.
- 14. (Original) The thermoplastic polyurethane composition of claim 13 wherein at least five of the criteria (A through F) are met.

- 15. (Original) The thermoplastic polyurethane composition of claim 14 wherein all six of the criteria (A through F) are met.
- 16. (Original) The thermoplastic polyurethane composition of claim 13 wherein  $T_{CN}$  is 0.85 or less,  $T_{SN}$  is 0.35 or greater,  $V_f(T_m + 15)$  is 6 or less,  $V_f(T_m + 35)$  is 4 or less,  $V_{ft}$  is 9 or less, and  $V_t$  is 3.5 or less.
- 17. (Original) The thermoplastic polyurethane composition of claim 16 wherein at least five of the criteria are met.
- 18. (Original) The thermoplastic polyurethane composition of claim 17 wherein all six of the criteria are met.
- 19. (Original) A coated fabric wherein said coating comprises the thermoplastic polyurethane composition of claim 1.
- 20. (Original) A coated fabric wherein said coating comprises the thermoplastic polyurethane composition of claim 13.
- 21. (Original) A coated fabric wherein said coating comprises the thermoplastic polyurethane composition of claim 16.
- 22. (Original) A coated fabric wherein said coating comprises the thermoplastic polyurethane composition of claim 16, and wherein said fabric comprises nylon, polyester, or polyolefin.

- 23. (Original) A sheet or a film comprising the thermoplastic polyurethane composition of claim 1.
- 24. *(Original)* A sheet or a film comprising the thermoplastic polyurethane composition of claim 13.
- 25. (Original) A sheet or a film comprising the thermoplastic polyurethane composition of claim 16.
- 26. (Original) A sheet or film comprising the thermoplastic polyurethane composition of claim 17.
- 27. (Original) A conveyor belt comprising the thermoplastic polyurethane composition of claim 1.
- 28. (Original) A conveyer belt comprising the thermoplastic polyurethane composition of claim 13.
- 29. (Original) A conveyer belt comprising the thermoplastic polyurethane composition of claim 16.
- 30. (Original) A conveyer belt comprising the thermoplastic polyurethane composition of claim 17.
- 31. (Original) An inflatable article, an apparel, or a storage bag comprising the thermoplastic polyurethane composition of claim 1.

- 32. (Original) An inflatable article, an apparel, or a storage bag comprising the thermoplastic polyurethane composition of claim 13.
- 33. (Original) An inflatable article, an apparel, or a storage bag comprising the thermoplastic polyurethane composition of claim 16.
- 34. (Original) An inflatable article, an apparel, or a storage bag comprising the thermoplastic polyurethane composition of claim 17.
- 35. *(Currently Amended)* A process for producing a thermoplastic polyurethane polymer comprising reacting:
- A. a polyester polyol having a number average molecular weight of from about 500 to about 5,000;
- B. from about 1 to about 50 parts by weight of a polyether co-polyol comprising poly(tetramethylene ether glycol) per 100 parts by weight of the combined total amount of said polyester polyol and said polyether co-polyol;
  - C. a polyisocyanate;
- D. a symmetrical chain extender selected from the group consisting of 1,6-hexanediol, 1,3-propanediol, 1,5-pentanediol, 1,4-butanediol, 1,4-cyclohexanedimethanol (CHDM), hydroquinone di(β-hydroxyethyl)ether (HQEE), 1,4-benzenedimethylol, and combinations thereof;
- E. from about 1 to about 50 moles of a co-chain extender selected from the group consisting of 1,3-butanediol, neopentyl glycol, dipropylene glycol, diethylene glycol, di(β-hydroxyethyl) resorcinol, 1,2-propylene glycol, and combinations thereof that is asymmetric or of

Docket No. 202ES048A

Serial No. 10/785,529

October 16, 2007

Page 9

a different chain length than said symmetrical chain extender or is non-linear or contains a

heteroatom co-chain extender per 100 moles of said symmetrical chain extender; and

wherein the ratio of the molar percent ratio of said co-chain extender to said symmetrical

chain extender to weight percent of said polyether co-polyol to the combined total weight of said

polyester polyol and said polyether co-polyol, is from about 0.1 to about 10.

36. (Original) The process of claim 35 further comprising a thermoplastic polyurethane catalyst

in an amount less than about 1000 parts by weight per million parts by weight of the combined

weight of said polyester polyol, polyether co-polyol, polyisocyanate, symmetrical chain extender

and said co-chain extender.

37. (Previously Presented) The process of claim 36 wherein said process is conducted in a twin

screw extruder where the reactants are brought together and reacted.

38. (Original) The process of claim 37 wherein said process is conducted at from about 110°C

to about 200°C.

39. (Original) The process of claim 38 wherein the reaction time is from about 2 to about 3

minutes.

40. (Original) The process of claim 38 wherein said co-chain extender is used at a level of from

about 5 to about 10 moles per 100 moles of said symmetrical chain extender.

41. (Previously Presented) The process of claim 40 wherein said polyether co-polyol is used at

a level of from about 5 to about 20 parts by weight per 100 parts by weight of the combined total

amount of said polyester polyol and said polyether co-polyol.

## 42. (Currently Amended) The process of claim 35

- A. wherein said polyester polyol is derived from an acid selected from the group consisting of adipic acid, suberic acid, sebacic acid, azelaic acid, and combinations thereof reacted with a glycol selected from the group consisting of 1,4-butanediol, diethylene glycol, 1,6-hexanediol, neopentyl glycol and combinations thereof;
- B. wherein said polyether co-polyol is selected from the group consisting of poly(tetramethylene ether glycol), poly(ethylene oxide), poly(propylene oxide), poly(propylene oxide), and mixtures thereof;
- C. wherein said polyisocyanate is a diisocyanate selected from the group consisting of MDI, H<sub>12</sub> MDI, and mixtures thereof;
- D. wherein said symmetrical chain extender is selected from the group consisting of 1,6-hexanediol, 1,3-propanediol, 1,5-pentane diol, 1,4-butanediol, 1,4-cyclohexanedimethanol, hydroquinone di(ß-hydroxyethyl) ether, 1,4-benzenedimethylol, and mixtures thereof; and
- E. wherein said co-chain extender is selected from the group consisting of 1,3-butanediol, neopentyl glycol, diethylene glycol, dipropylene glycol, di(β-hydroxyethyl) resorcinol, 1,2-propylene glycol, and mixture thereof.